


## TSC1417 TRANSISTOR (NPN)

### FEATURES

- General Purpose Switching and Amplification.



### ORDERING INFORMATION

Part Number	Package	Packing Method	Pack Quantity
TSC1417	TO-92	Bulk	1000pcs/Bag
TSC1417-TA	TO-92	Tape	2000pcs/Box

### MAXIMUM RATINGS ( $T_a=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Value	Unit
$V_{CBO}$	Collector-Base Voltage	20	V
$V_{CEO}$	Collector-Emitter Voltage	15	V
$V_{EBO}$	Emitter-Base Voltage	3	V
$I_C$	Collector Current	30	mA
$P_c$	Collector Power Dissipation	625	mW
$R_{\theta JA}$	Thermal Resistance From Junction To Ambient	200	°C/W
$T_J, T_{stg}$	Operation Junction and Storage Temperature Range	-55~+150	°C

$T_a=25^\circ C$  unless otherwise specified

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
<b>Collector-base breakdown voltage</b>	$V_{(BR)CBO}$	$I_C=0.1mA, I_E=0$	20			V
<b>Collector-emitter breakdown voltage</b>	$V_{(BR)CEO}$	$I_C=1mA, I_B=0$	15			V
<b>Emitter-base breakdown voltage</b>	$V_{(BR)EBO}$	$I_E=0.1mA, I_C=0$	3			V
<b>Collector cut-off current</b>	$I_{CBO}$	$V_{CB}=10V, I_E=0$			1	$\mu A$
<b>Emitter cut-off current</b>	$I_{EBO}$	$V_{EB}=2V, I_C=0$			1	$\mu A$
<b>DC current gain</b>	$h_{FE}$	$V_{CE}=6V, I_C=1mA$	29		270	
<b>Collector-emitter saturation voltage</b>	$V_{CE(sat)}$	$I_C=10mA, I_B=1mA$			0.5	V
<b>Base-emitter saturation voltage</b>	$V_{BE(sat)}$	$I_C=10mA, I_B=1mA$			1.42	V
<b>Transition frequency</b>	$f_T$	$V_{CE}=6V, I_C=1mA$		300		MHz

#### CLASSIFICATION OF $h_{FE}$

RANK	D	E	F	G	H	I	J
RANGE	29-45	39-60	54-80	72-108	97-146	132-198	180-270