


## Description

<b>Features</b> <ul style="list-style-type: none"> <li>● 30V,180A</li> <li>● <math>R_{DS(ON)} &lt; 2.4m\Omega @ V_{GS} = 10V</math></li> <li>● <math>R_{DS(ON)} &lt; 5m\Omega @ V_{GS} = 4.5V</math></li> <li>● Advanced Trench Technology</li> <li>● Excellent <math>R_{DS(ON)}</math> and Low Gate Charge</li> <li>● Lead free product is acquired</li> </ul>	<b>Application</b> <ul style="list-style-type: none"> <li>● Load Switch</li> <li>● PWM Application</li> <li>● Power management</li> </ul> <p style="text-align: center;">100% UIS 100% <math>\Delta Vds</math></p>
 TO-263	 Schematic Diagram

## Package Marking and Ordering Information

Device Marking	Device	OUTLINE	Device Package	Reel Size	Reel (PCS)	Per Carton (PCS)
VSM180N03-T3	VSM180N03	TAPING	TO-263	13inch	800	4000

## Absolute Maximum Ratings (T<sub>C</sub>=25°C unless otherwise specified)

Symbol	Parameter	Max.	Units
V <sub>DSS</sub>	Drain-Source Voltage	30	V
V <sub>GSS</sub>	Gate-Source Voltage	±20	V
I <sub>D</sub>	Continuous Drain Current	T <sub>C</sub> = 25°C	180
		T <sub>C</sub> = 100°C	117
I <sub>DM</sub>	Pulsed Drain Current <sup>note1</sup>	720	A
E <sub>AS</sub>	Single Pulsed Avalanche Energy <sup>note2</sup>	240	mJ
P <sub>D</sub>	Power Dissipation	T <sub>C</sub> = 25°C	130
R <sub>θJC</sub>	Thermal Resistance, Junction to Case	1.15	°C/W
T <sub>J</sub> , T <sub>STG</sub>	Operating and Storage Temperature Range	-55 to +175	°C

**Electrical Characteristics** ( $T_C=25^{\circ}\text{C}$  unless otherwise specified)







Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
<b>Off Characteristic</b>						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	30	-	-	V
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS}=30V, V_{GS}=0V,$	-	-	1.0	$\mu A$
$I_{GSS}$	Gate to Body Leakage Current	$V_{DS}=0V, V_{GS}=\pm 20V$	-	-	$\pm 100$	nA
<b>On Characteristics</b>						
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	1.0	1.5	2.5	V
$R_{DS(on)}$	Static Drain-Source on-Resistance <small>note3</small>	$V_{GS}=10V, I_D=30A$	-	1.95	2.4	m $\Omega$
		$V_{GS}=4.5V, I_D=20A$	-	3.5	5	
<b>Dynamic Characteristics</b>						
$C_{iss}$	Input Capacitance	$V_{DS}=15V, V_{GS}=0V,$ $f=1.0\text{MHz}$	-	4930	-	pF
$C_{oss}$	Output Capacitance		-	682	-	pF
$C_{rss}$	Reverse Transfer Capacitance		-	566	-	pF
$Q_g$	Total Gate Charge	$V_{DS}=15V, I_D=30A,$ $V_{GS}=10V$	-	70	-	nC
$Q_{gs}$	Gate-Source Charge		-	10	-	nC
$Q_{gd}$	Gate-Drain("Miller") Charge		-	15	-	nC
<b>Switching Characteristics</b>						
$t_{d(on)}$	Turn-on Delay Time	$V_{DS}=15V,$ $I_D=30A, R_{GEN}=3\Omega,$ $V_{GS}=10V$	-	10	-	ns
$t_r$	Turn-on Rise Time		-	6.5	-	ns
$t_{d(off)}$	Turn-off Delay Time		-	75	-	ns
$t_f$	Turn-off Fall Time		-	18	-	ns
<b>Drain-Source Diode Characteristics and Maximum Ratings</b>						
$I_S$	Maximum Continuous Drain to Source Diode Forward Current		-	-	180	A
$I_{SM}$	Maximum Pulsed Drain to Source Diode Forward Current		-	-	720	A
$V_{SD}$	Drain to Source Diode Forward Voltage	$V_{GS}=0V, I_S=30A$	-	-	1.2	V
$t_{rr}$	Body Diode Reverse Recovery Time	$I_F=20A, di/dt=100A/\mu s$	-	30	-	ns
$Q_{rr}$	Body Diode Reverse Recovery Charge		-	15	-	nC

Notes:1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature


 2. EAS condition:  $T_J=25^{\circ}\text{C}, V_{DD}=15V, V_G=10V, L=0.5\text{mH}, R_G=25\Omega, I_{AS}=31A$ 

 3. Pulse Test: Pulse Width $\leq 300\mu s$ , Duty Cycle $\leq 0.5\%$


## Typical Performance Characteristics

**Figure 1: Output Characteristics**

**Figure 2: Typical Transfer Characteristics**

**Figure 3: On-resistance vs. Drain Current**

**Figure 4: Body Diode Characteristics**

**Figure 5: Gate Charge Characteristics**

**Figure 6: Capacitance Characteristics**



**Figure 7:** Normalized Breakdown Voltage vs. Junction Temperature




**Figure 8:** Normalized on Resistance vs. Junction Temperature




**Figure 9:** Maximum Safe Operating Area






**Figure 10:** Maximum Continuous Drain Current vs. Case Temperature



**Figure.11:** Maximum Effective Transient Thermal Impedance, Junction-to-Case




**Figure1:Gate Charge Test Circuit & Waveform**

**Figure 2: Resistive Switching Test Circuit & Waveforms**

**Figure 3:Unclamped Inductive Switching Test Circuit & Waveforms**