

Description

The series of devices uses **Super Trench II** technology that is uniquely optimized to provide the most efficient high frequency switching performance. Both conduction and switching power losses are minimized due to an extremely low combination of $R_{DS(ON)}$ and Q_g . This device is ideal for high-frequency switching and synchronous rectification.

Application


- DC/DC Converter
- Ideal for high-frequency switching and synchronous rectification

General Features

- $V_{DS} = 100V, I_D = 280A$
- $R_{DS(ON)} = 1.85m\Omega$, typical @ $V_{GS} = 10V$
- Excellent gate charge x $R_{DS(on)}$ product(FOM)
- Very low on-resistance $R_{DS(on)}$
- 175 °C operating temperature
- Pb-free lead plating



TO-247



Schematic Diagram

Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
VST10N018-T7	VST10N018	TO-247	-	-	-

Absolute Maximum Ratings ($T_c=25^\circ C$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	100	V
Gate-Source Voltage	V_{GS}	± 20	V
Drain Current-Continuous	I_D	280	A
Drain Current-Continuous($T_c=100^\circ C$)	$I_D (100^\circ C)$	200	A
Pulsed Drain Current	I_{DM}	980	A
Maximum Power Dissipation	P_D	365	W
Derating factor		2.43	W/°C
Single pulse avalanche energy ^(Note 4)	E_{AS}	2784	mJ
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 To 175	°C

Thermal Characteristic

Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	0.41	°C/W
--------------------------------------	-----------------	------	------

Electrical Characteristics ($T_c=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_D=250\mu\text{A}$	100		-	V
Zero Gate Voltage Drain Current	I_{DSS}	$\text{V}_{\text{DS}}=100\text{V}, \text{V}_{\text{GS}}=0\text{V}$	-	-	1	μA
Gate-Body Leakage Current	I_{GSS}	$\text{V}_{\text{GS}}=\pm 20\text{V}, \text{V}_{\text{DS}}=0\text{V}$	-	-	± 100	nA
On Characteristics (Note 2)						
Gate Threshold Voltage	$\text{V}_{\text{GS(th)}}$	$\text{V}_{\text{DS}}=\text{V}_{\text{GS}}, \text{I}_D=250\mu\text{A}$	2.0	3.0	4.0	V
Drain-Source On-State Resistance	$\text{R}_{\text{DS(ON)}}$	$\text{V}_{\text{GS}}=10\text{V}, \text{I}_D=140\text{A}$	-	1.85	2.3	$\text{m}\Omega$
Forward Transconductance	g_{FS}	$\text{V}_{\text{DS}}=5\text{V}, \text{I}_D=140\text{A}$		200	-	S
Dynamic Characteristics (Note3)						
Input Capacitance	C_{iss}	$\text{V}_{\text{DS}}=50\text{V}, \text{V}_{\text{GS}}=0\text{V},$ $F=1.0\text{MHz}$	-	17000	-	PF
Output Capacitance	C_{oss}		-	1500	-	PF
Reverse Transfer Capacitance	C_{rss}		-	77	-	PF
Switching Characteristics (Note 3)						
Turn-on Delay Time	$t_{\text{d(on)}}$	$\text{V}_{\text{DD}}=50\text{V}, \text{I}_D=140\text{A}$ $\text{V}_{\text{GS}}=10\text{V}, \text{R}_G=1.6\Omega$	-	37	-	nS
Turn-on Rise Time	t_r		-	29	-	nS
Turn-Off Delay Time	$t_{\text{d(off)}}$		-	82	-	nS
Turn-Off Fall Time	t_f		-	34	-	nS
Total Gate Charge	Q_g	$\text{V}_{\text{DS}}=50\text{V}, \text{I}_D=140\text{A},$ $\text{V}_{\text{GS}}=10\text{V}$	-	252	-	nC
Gate-Source Charge	Q_{gs}		-	72	-	nC
Gate-Drain Charge	Q_{gd}		-	63	-	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage (Note 3)	V_{SD}	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_s=140\text{A}$	-		1.2	V
Diode Forward Current (Note 2)	I_s		-	-	280	A
Reverse Recovery Time	t_{rr}	$\text{T}_J = 25^\circ\text{C}, \text{I}_F = 140\text{A}$ $d\text{i}/dt = 100\text{A}/\mu\text{s}$ (Note2)	-	105	-	nS
Reverse Recovery Charge	Q_{rr}		-	290	-	nC

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.
3. Guaranteed by design, not subject to production
4. EAS condition : $\text{T}_J=25^\circ\text{C}, \text{V}_{\text{DD}}=50\text{V}, \text{V}_{\text{G}}=10\text{V}, \text{L}=0.5\text{mH}, \text{R}_G=25\Omega$

Typical Electrical and Thermal Characteristics




Figure 1 Output Characteristics




Figure 4 R_{DSON} -Junction Temperature




Figure 2 Transfer Characteristics




Figure 5 Gate Charge




Figure 3 R_{DSON} - Drain Current




Figure 6 Source- Drain Diode Forward




Figure 7 Capacitance vs Vds




Figure 9 Power De-rating




Figure 8 Safe Operation Area




Figure 10 Current De-rating




Figure 11 Normalized Maximum Transient Thermal Impedance