

Description


The series of devices uses **Super Trench II** technology that is uniquely optimized to provide the most efficient high frequency switching performance. Both conduction and switching power losses are minimized due to an extremely low combination of $R_{DS(ON)}$ and Q_g . This device is ideal for high-frequency switching and synchronous rectification.

Application


- DC/DC Converter
- Ideal for high-frequency switching and synchronous rectification

General Features

- $V_{DS} = 100V, I_D = 14A$
- $R_{DS(ON)} = 8.4m\Omega$, typical@ $V_{GS} = 10V$
- $R_{DS(ON)} = 10.0m\Omega$, typical@ $V_{GS} = 4.5V$
- Excellent gate charge $\times R_{DS(on)}$ product(FOM)
- Very low on-resistance $R_{DS(on)}$
- 175 °C operating temperature
- Pb-free lead plating



SOP-8



Schematic Diagram

Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
VST10N084-S8	VST10N084	SOP-8	-	-	-

Absolute Maximum Ratings ($T_c=25^\circ C$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	100	V
Gate-Source Voltage	V_{GS}	± 20	V
Drain Current-Continuous	I_D	14	A
Drain Current-Continuous($T_c=100^\circ C$)	$I_D (100^\circ C)$	10	A
Pulsed Drain Current	I_{DM}	300	A
Maximum Power Dissipation	P_D	3.5	W
Single pulse avalanche energy ^(Note 4)	E_{AS}	350	mJ
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 To 150	°C

Thermal Characteristic

Thermal Resistance, Junction-to-Ambient	$R_{\theta JA}$	36	°C/W
---	-----------------	----	------

Electrical Characteristics ($T_c=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_D=250\mu\text{A}$	100	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	$\text{V}_{\text{DS}}=100\text{V}, \text{V}_{\text{GS}}=0\text{V}$	-	-	1	μA
Gate-Body Leakage Current	I_{GSS}	$\text{V}_{\text{GS}}=\pm20\text{V}, \text{V}_{\text{DS}}=0\text{V}$	-	-	±100	nA
On Characteristics (Note 3)						
Gate Threshold Voltage	$\text{V}_{\text{GS}(\text{th})}$	$\text{V}_{\text{DS}}=\text{V}_{\text{GS}}, \text{I}_D=250\mu\text{A}$	1.2	1.7	2.2	V
Drain-Source On-State Resistance	$\text{R}_{\text{DS}(\text{ON})}$	$\text{V}_{\text{GS}}=10\text{V}, \text{I}_D=14\text{A}$	-	8.4	9.2	$\text{m}\Omega$
		$\text{V}_{\text{GS}}=4.5\text{V}, \text{I}_D=14\text{A}$	-	10.0	12.0	$\text{m}\Omega$
Forward Transconductance	g_{FS}	$\text{V}_{\text{DS}}=5\text{V}, \text{I}_D=14\text{A}$		60	-	S
Dynamic Characteristics (Note 3)						
Input Capacitance	C_{iss}	$\text{V}_{\text{DS}}=50\text{V}, \text{V}_{\text{GS}}=0\text{V}, \text{F}=1.0\text{MHz}$	-	3650	-	pF
Output Capacitance	C_{oss}		-	315	-	pF
Reverse Transfer Capacitance	C_{rss}		-	22	-	pF
Switching Characteristics (Note 3)						
Turn-on Delay Time	$t_{\text{d}(\text{on})}$	$\text{V}_{\text{DD}}=50\text{V}, \text{I}_D=14\text{A}$ $\text{V}_{\text{GS}}=10\text{V}, \text{R}_G=1.6\Omega$	-	16	-	nS
Turn-on Rise Time	t_r		-	11	-	nS
Turn-Off Delay Time	$t_{\text{d}(\text{off})}$		-	35	-	nS
Turn-Off Fall Time	t_f		-	9	-	nS
Total Gate Charge	Q_g	$\text{V}_{\text{DS}}=50\text{V}, \text{I}_D=14\text{A}, \text{V}_{\text{GS}}=10\text{V}$	-	70	-	nC
Gate-Source Charge	Q_{gs}		-	14.5	-	nC
Gate-Drain Charge	Q_{gd}		-	16.8	-	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage (Note 2)	V_{SD}	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_s=14\text{A}$	-	-	1.2	V
Diode Forward Current	I_s		-	-	14	A
Reverse Recovery Time	t_{rr}	$\text{T}_J = 25^\circ\text{C}, \text{I}_F = 14\text{A}$ $d\text{i}/dt = 100\text{A}/\mu\text{s}$ (Note 3)	-	60	-	nS
Reverse Recovery Charge	Q_{rr}		-	106	-	nC

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.
3. Guaranteed by design, not subject to production
4. EAS condition : $\text{T}_J=25^\circ\text{C}, \text{V}_{\text{DD}}=50\text{V}, \text{V}_G=10\text{V}, \text{L}=0.25\text{mH}, \text{R}_G=25\Omega$

Typical Electrical and Thermal Characteristics




Figure 1 Output Characteristics




Figure 4 Gate Charge




Figure 2 Transfer Characteristics




Figure 5 Source- Drain Diode Forward




Figure 3 Rdson- Drain Current









Figure 6 Capacitance vs Vds


Figure 7 Power De-rating

Figure 9 Current De-rating

Figure 8 Safe Operation Area

Figure 10 Rdson-Junction Temperature

Figure 11 Normalized Maximum Transient Thermal Impedance