

Features

- Excellent $R_{DS(ON)}$ and Low Gate Charge
- 100% UIS Tested
- 100% ΔV_{ds} Tested
- Halogen-free; RoHS-compliant

Applications


- Load Switch
- PWM Application
- Power Management

Product Summary

Parameters	Value	Unit
V_{DSS}	60	V
$V_{GS(th)_{Typ}}$	3.0	V
$I_D(@V_{GS}=10V)$	120	A
$R_{DS(ON)_{Typ}}(@V_{GS}=10V)$	4.2	$m\Omega$



TO-220



Schematic

Ordering Information

Device	Marking	MSL	Form	Package	Tube(pcs)	Per Carton (pcs)
VSM120N06-TC	VSM120N06	N/A	Tube	TO-220	50	5000

Absolute Maximum Ratings (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter		Value	Unit
V _{DS}	Drain-to-Source Voltage		60	V
V _{GS}	Gate-to-Source Voltage		±25	V
I _D	Continuous Drain Current	T _C = 25°C	120	A
		T _C = 100°C	76	
I _{DM}	Pulsed Drain Current ⁽¹⁾		Refer to Fig.4	A
E _{AS}	Single Pulsed Avalanche Energy ⁽²⁾		282	mJ
P _D	Power Dissipation	T _C = 25°C	139	W
		T _C = 100°C	56	
T _J , T _{STG}	Junction & Storage Temperature Range		-55 to 150	°C

Thermal Characteristics





Symbol	Parameter	Max	Unit
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient ⁽³⁾	71	$^\circ\text{C/W}$
$R_{\theta JC}$	Thermal Resistance, Junction to Case	0.9	

Electrical Characteristics ($T_J = 25^\circ\text{C}$ unless otherwise specified)







Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
Off Characteristics						
V _{(BR)DSS}	Drain-Source Breakdown Voltage	I _D = 250 μA, V _{GS} = 0V	60	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 60V, V _{GS} = 0V	-	-	1.0	μA
I _{GSS}	Gate-Body Leakage Current	V _{DS} = 0V, V _{GS} = ±25V	-	-	±100	nA
On Characteristics						
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250 μA	2.1	3.0	4.0	V
R _{DS(ON)}	Static Drain-Source ON-Resistance ⁽⁴⁾	V _{GS} = 10V, I _D = 30A	-	4.2	6.0	mΩ
Dynamic Characteristics						
R _g	Gate Resistance	f = 1MHz	-	1.1	-	Ω
C _{iss}	Input Capacitance	V _{GS} = 0V, V _{DS} = 30V, f = 1MHz	3688	5163	6970	pF
C _{oss}	Output Capacitance		265	370	500	pF
C _{rss}	Reverse Transfer Capacitance		234	327	442	pF
Q _g	Total Gate Charge	V _{GS} = 0 to 10V V _{DS} = 30V, I _D = 30A	80	112	151	nC
Q _{gs}	Gate Source Charge		22	31	41	nC
Q _{gd}	Gate Drain("Miller") Charge		28	39	53	nC
Switching Characteristics						
t _{d(on)}	Turn-On DelayTime	V _{GS} = 10V, V _{DD} = 30V I _D = 30A, R _{GEN} = 3 Ω	-	20	-	ns
t _r	Turn-On Rise Time		-	43	-	ns
t _{d(off)}	Turn-Off DelayTime		-	53	-	ns
t _f	Turn-Off Fall Time		-	23	-	ns
Body Diode Characteristics						
I _S	Maximum Continuous Body Diode Forward Current		-	-	120	A
I _{SM}	Maximum Pulsed Body Diode Forward Current		-	-	480	A
V _{SD}	Body Diode Forward Voltage	V _{GS} = 0V, I _S = 30A	-		1.2	V
t _{rr}	Body Diode Reverse Recovery Time	I _F = 30A, di/dt = 100A/us	20	28	37	ns
Q _{rr}	Body Diode Reverse Recovery Charge		-	31	-	nC

- Notes:
1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature.
 2. E_{AS} condition: Starting $T_J = 25^\circ\text{C}$, $V_{DD} = 30\text{V}$, $V_{GS} = 10\text{V}$, $R_G = 25\text{ohm}$, $L = 0.5\text{mH}$, $I_{AS} = 33.6\text{A}$, $V_{DD} = 0\text{V}$ during time in avalanche.
 3. $R_{\theta JA}$ is measured with the device mounted on FR-4 substrate PC board, 2oz copper, with minimum recommended pad layout.
 4. Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 0.5\%$.

Typical Performance Characteristics

Figure 1: Power De-rating

Figure 2: Current De-rating

Figure 3: Normalized Maximum Transient Thermal Impedance

Figure 4: Peak Current Capacity


Typical Performance Characteristics

Figure 5: Output Characteristics

Figure 6: Typical Transfer Characteristics

Figure 7: On-resistance vs. Drain Current

Figure 8: Body Diode Characteristics

Figure 9: Gate Charge Characteristics

Figure 10: Capacitance Characteristics


Typical Performance Characteristics

Figure 11: Normalized Breakdown voltage vs. Junction Temperature




Figure 12: Normalized on Resistance vs. Junction Temperature




Figure 13: Normalized Threshold Voltage vs. Junction Temperature




Figure 14: $R_{DS(ON)}$ vs. V_{GS}





Figure 15: Maximum Safe Operating Area



Test Circuit




Figure 1: Gate Charge Test Circuit & Waveform




Figure 2: Resistive Switching Test Circuit & Waveform




Figure 3: Unclamped Inductive Switching Test Circuit& Waveform




Figure 4: Diode Recovery Test Circuit & Waveform