

Key performance:

- $V_{CE}=1350V$
- $I_C=15A@T_C=100^{\circ}C$
- $V_{CE(sat)}=1.6V$


Features:

- Trench and field-stop technology
- Low collector to emitter saturation voltage
- Easy parallel switching capability
- High ruggedness performance
- RoHS compliant

Applications:

- Induction cooking
- Resonant converters

TO-3P



Package parameters

Type	Marking	Package	Packaging Method
VSG15N135-TP	VSG15N135	TO-3P	Tube

Maximum ratings

Symbol	Parameter	Values	Unit
V_{CES}	Collector-emitter voltage	1350	V
V_{GES}	Gate-emitter voltage	± 20	V
I_C	Continuous collector current ($T_C=25^{\circ}\text{C}$)	30	A
	Continuous collector current ($T_C=100^{\circ}\text{C}$)	15	A
I_{CM}	Pulsed collector current, t_p limited by T_{vjmax}	60	A
I_F	Diode continuous forward current ($T_C=100^{\circ}\text{C}$)	15	A
I_{FM}	Diode maximum current, t_p limited by T_{vjmax}	60	A
P_{tot}	Power dissipation ($T_C=25^{\circ}\text{C}$)	375	W
	Power dissipation ($T_C=100^{\circ}\text{C}$)	187	W
T_{vj}	Operating junction temperature range	-40 to +175	$^{\circ}\text{C}$
T_{stg}	Storage temperature range	-55 to +150	$^{\circ}\text{C}$

Thermal characteristics

Symbol	Parameter	Values		Unit
		Typ.	Max.	
$R_{th(j-c)}$	Thermal resistance, junction to case for IGBT	-	0.4	K/ W
$R_{th(j-c)}$	Thermal resistance, junction to case for Diode	-	1.2	K/ W
$R_{th(j-a)}$	Thermal resistance, junction to ambient	-	39	K/ W

Electrical characteristics of IGBT ($T_{vj}=25^{\circ}\text{C}$ unless otherwise specified)

Static characteristics

Symbol	Parameter	Test condition	Values			Unit
			Min.	Typ.	Max.	
BV_{CES}	Collector-emitterbreakdown voltage	$V_{GE}=0V, I_C=250\mu A$	1350	-	-	V
I_{CES}	Collector-emitter leakage current	$V_{CE}=1350V, V_{GE}=0V$	-	-	100	μA
I_{GES}	Gate leakage current, forward	$V_{GE}=20V, V_{CE}=0V$	-	-	100	nA
	Gate leakage current, reverse	$V_{GE}=-20V, V_{CE}=0V$	-	-	-100	nA
$V_{GE(th)}$	Gate-emitter threshold voltage	$V_{GE}=V_{CE}, I_C=1mA$	5.5	6.0	6.5	V
$V_{CE(sat)}$	Collector-emitter saturation voltage	$V_{GE}=15V, I_C=15A$	-	1.6	-	V
		$V_{GE}=15V, I_C=15A, T_{vj}=175^{\circ}\text{C}$	-	2.05	-	V

Dynamic characteristics

Symbol	Parameter	Test condition	Values			Unit
			Min.	Typ.	Max.	
C_{ies}	Input capacitance	$V_{CE}=30V$ $V_{GE}=0V$ $f=1MHz$	-	2940	-	pF
C_{oes}	Output capacitance		-	35	-	pF
C_{res}	Reverse transfer capacitance		-	7	-	pF
Q_g	Total gate charge	$V_{CC}=1080V$ $V_{GE}=15V$ $I_C=15A$	-	85	-	nC

Switching characteristics

Symbol	Parameter	Test condition	Values			Unit
			Min.	Typ.	Max.	
$t_{d(on)}$	Turn-on delay time	$V_{CC}=600V$ $V_{GE}=0/15V$ $I_C=15A$ $R_G=10\Omega$ Inductive load	-	29	-	ns
t_r	Rise time		-	23	-	ns
$t_{d(off)}$	Turn-off delay time		-	145	-	ns
t_f	Fall time		-	213	-	ns
E_{on}	Turn-on energy		-	1.0	-	mJ
E_{off}	Turn-off energy		-	1.1	-	mJ
E_{ts}	Total switching energy		-	2.1	-	mJ
$t_{d(on)}$	Turn-on delay time	$V_{CC}=600V$ $V_{GE}=0/15V$ $I_C=15A$ $R_G=10\Omega, T_{vj}=175^\circ C$ Inductive load	-	27	-	ns
t_r	Rise time		-	26	-	ns
$t_{d(off)}$	Turn-off delay time		-	177	-	ns
t_f	Fall time		-	375	-	ns
E_{on}	Turn-on energy		-	1.1	-	mJ
E_{off}	Turn-off energy		-	1.5	-	mJ
E_{ts}	Total switching energy		-	2.6	-	mJ

Electrical characteristics of Diode ($T_{vj}=25^\circ C$ unless otherwise specified)

Symbol	Parameter	Test condition	Values			Unit
			Min.	Typ.	Max.	
V_F	Diode forward voltage	$I_F=15A$	-	1.55	-	V
		$I_F=15A, T_{vj}=175^\circ C$	-	1.4	-	V

Typical performance characteristics




Fig 1. Typical output characteristic ($T_{vj}=25^{\circ}\text{C}$)




Fig 2. Typical output characteristic ($T_{vj}=175^{\circ}\text{C}$)




Fig 3. Power dissipation as a function of T_c




Fig 4. Typical Gate charge




Fig 5. Typical $V_{GE(th)}$ as a function of T_{vj}
($I_c=1\text{mA}$)




Fig 6. Typical V_F as a function of T_{vj}

Typical performance characteristics




Fig 7. Typical V_{CEsat} as a function of T_{vj}




Fig 8. Typical I_F as a function of V_F




Fig 9. Typical switching time as a function of I_C




Fig 10. Typical switching times as a function of R_G




Fig 11. Typical switching energy losses as a function of I_C




Fig 12. Typical switching energy losses as a function of R_G

Typical performance characteristics




Fig 13. Typical capacitance as a function of V_{CE}
($f=1\text{MHz}$, $V_{GE}=0\text{V}$)





Fig 14. Transient thermal impedance of IGBT

Package dimension

TO-3P



Items	Values(mm)	
	MIN	MAX
A	15.00	16.00
B	19.20	20.60
C	4.60	5.00
D	1.40	1.60
E	0.90	1.10
F	0.50	0.70
G1	2.00	2.20
G2	3.00	3.20
H	3.00	3.70
I	2.30	2.50
L*	19.00	21.00
N	5.25	5.65
Φ P	3.10	3.30