


79L09 Three-terminal negative voltage regulator

FEATURES

- Maximum output current
 I_{OM} : 0.1A
- Output voltage
 V_o : -9V
- Continuous total dissipation
 P_D : 0.6 W ($T_a = 25^\circ\text{C}$)



ABSOLUTE MAXIMUM RATINGS (Operating temperature range applies unless otherwise specified)


Parameter	Symbol	Value	Unit
Input Voltage	V_i	-30	V
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	208.3	$^\circ\text{C/W}$
Operating Junction Temperature Range	T_{OPR}	-40~+125	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-65~+150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS AT SPECIFIED VIRTUAL JUNCTION TEMPERATURE ($V_i = -16\text{V}$, $I_o = 40\text{mA}$, $C_i = 0.33\mu\text{F}$, $C_o = 0.1\mu\text{F}$, unless otherwise specified)






Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Output Voltage	V_o	$T_J = 25^\circ\text{C}$	-8.73	-9.0	-9.27	V
		$-12\text{V} \leq V_i \leq -24\text{V}$, $I_o = 1\text{mA} - 40\text{mA}$	-8.55	-9.0	-9.45	V
		$I_o = 1\text{mA} - 70\text{mA}$	-8.55	-9.0	-9.45	V
Load Regulation	ΔV_o	$I_o = 1\text{mA} - 100\text{mA}$, $T_J = 25^\circ\text{C}$		19	90	mV
		$I_o = 1\text{mA} - 40\text{mA}$, $T_J = 25^\circ\text{C}$		11	40	mV
Line Regulation	ΔV_o	$-12\text{V} \leq V_i \leq -24\text{V}$, $T_J = 25^\circ\text{C}$		45	175	mV
		$-13\text{V} \leq V_i \leq -24\text{V}$, $T_J = 25^\circ\text{C}$		40	125	mV
Quiescent Current	I_q	$T_J = 25^\circ\text{C}$		4.1	6.0	mA
Quiescent Current Change	ΔI_q	$-13\text{V} \leq V_i \leq -24\text{V}$			1.5	mA
	ΔI_q	$1\text{mA} \leq V_i \leq 40\text{mA}$			0.1	mA
Output Noise Voltage	V_N	$10\text{Hz} \leq f \leq 100\text{KHz}$, $T_J = 25^\circ\text{C}$		58		$\mu\text{V}/V_o$
Ripple Rejection	RR	$-15\text{V} \leq V_i \leq -24\text{V}$, $f = 120\text{Hz}$		45		dB
Dropout Voltage	V_d	$T_J = 25^\circ\text{C}$		1.7		V

* Pulse test.

TYPICAL APPLICATION



Note: Bypass capacitors are recommended for optimum stability and transient response and should be located as close as possible to the regulators

Output Characteristics

Dropout Characteristics

Quiescent Current vs Input Voltage

Current Cut-offGrid Voltage

Output Voltage vs Junction Temperature

Power Derating Curve
